



Project / Type

Notes

Count / Date



General
Showcase , Recessed
white aluminium , RAL 9006 <sup>1</sup>
IP20
Interior
1250 lm
1090 lm/m
optical inset 65 lm/W <sup>2</sup>

LED
3000 K
CRI ≥ 95
L80 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 102 , R <sub>r</sub> : 94 , R <sub>(1-15)</sub> : 95
MR 0.61
MDER 0.55

Optical
asymmetric

Electrical
excl. driver
24 V
fixture 28.8 W
optical inset 19.3 W
PC3
25 W/m
24 V

Physical
length 1200 mm
width 9 mm
height 9 mm


<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

Installation instructions



Miniature linear light inset made of aluminium; tubular design; surface lacquered in white aluminium; optionally for recessed or surface mounting (available as an accessory); plug and play electrical connector system for toolless mounting; different connectors for mechanical and electrical connection available - for flexible system design (available as an accessory); fitted with LED light points; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 95; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; asymmetric radiation characteristic; light inset rotatable; degree of protection IP20; PC3; 24 V; accessories are listed separately; light source replaceable by an authorized professional;

Light distribution



Product drawing

