

# FELT 9 acoustic panel


091-72W-2950x0295-000



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling / Wall | Surface \_\_\_\_\_

white \_\_\_\_\_

fire resistance class: B-s1, d0 \_\_\_\_\_

PET felt (made of at least 50% post-consumer recycled material) \_\_\_\_\_

## Physical

length 2950 mm | width 295 mm | height 9 mm \_\_\_\_\_

Packaging unit: 5 pcs. \_\_\_\_\_

## Acoustics

Alpha w ( $\alpha_w$ ) up to 0.85 <sup>1</sup> \_\_\_\_\_

SAC (sound absorption class) up to B <sup>1</sup> \_\_\_\_\_

NRC up to 0.8 <sup>1</sup> \_\_\_\_\_

SAA up to 0.8 <sup>1</sup> \_\_\_\_\_

<sup>1</sup> Acoustic data calculations based on FELT 9 full plate, cavity 20cm

Acoustic element made of 9 mm thick, high quality, self-supporting, at least 50 % recycled PET felt with sound absorbing properties; cut rectangular; high quality visual and tactile surface, white; colour may deviate; can be used as wall or ceiling covering to significantly improve room acoustics; Packaging unit: 5 pcs.

## Product drawing

