

BETO direct / indirect power

free standing U-shape

074-69540T8R



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|-----------------------------------|--|
| Floor Standing | |
| black RAL 9005 ¹ | |
| Reflector chrome | |
| IP20 | |
| indirect 5740 lm direct 1750 lm | |
| total 7490 lm | |

LED

| | |
|--|--|
| 3000 K | |
| CRI ≥ 90 | |
| L90 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 99 R _f : 91 R ₍₁₋₁₅₎ : 89 | |
| MR 0.61 MDER 0.55 | |

Optical

| | |
|---|--|
| Reflector asymmetric | |
| UGR ≤ 13 | |
| PstLM ≤ 1.0 ² SVM ≤ 0.4 ² | |

Electrical


| | |
|--------------------------------|--|
| Loxone Air / touch DIM on pole | |
| PC1 220-240 V | |
| system 66 W | |
| system 113 lm/W ³ | |

Physical


| | |
|---|--|
| U-shape | |
| length 1055 mm width 42 mm height 2100 mm | |

Free standing luminaire from extruded aluminium profile in angular design; extremely slim design (only 42 x 42 mm); square downpipe; pedestal with recess for table base (U-shape); surface black powder coated; direct/indirect illumination characteristic; direct light component with high gloss reflector + faceted design and asymmetric radiation characteristic; Reflector chrome; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination; UGR ≤ 13; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. Loxone Air module for easy integration into the Loxone home and building automation system; including TOUCH DIM miniature push-button; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



BETO direct / indirect power

free standing U-shape
074-69540T8R



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Factor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 13 |
| B13 | 17 |
| B16 | 21 |
| B20 | 27 |
| C10 | 21 |
| C13 | 28 |
| C16 | 35 |
| C20 | 45 |

