

BETO direct / indirect TW

power

suspended

074-62D6048B



Project / Type

Notes

Count / Date



General
Ceiling Suspended
black RAL 9005 ¹
Reflector dark chrome
IP20
indirect 3050 lm direct 2120 lm
total 5170 lm
4320 lm/m

LED
3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 R _r : 91 R ₍₁₋₁₅₎ : 89
MR 0.61 MDER 0.55


Optical
Reflector symmetric
UGR ≤ 10 ≥ 65° < 1500 cd/m ²
PstLM ≤ 1.0 ^{2 3 4} SVM ≤ 0.4 ^{2 3 4}

Electrical
DALI-2 D/I separately controllable 2 DALI Addr.
PC1 220-240 V
system 53 W
system 98 lm/W ⁵
44 W/m


Physical
length 1857 mm width 42 mm height 42 mm
3 kg

Luminaire housing made of extruded aluminium profile; extremely slim design (only 42 x 42 mm); light tight final end caps made of aluminium; no visible screws; angular design; surface black powder coated; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; incl. feed (black); extruded profile for improved thermal management; high gloss reflector with faceted design; Reflector dark chrome; direct/indirect illumination characteristic; light colour direct light component: 3000 K; light colour indirect light component: tunable white diodes (2700-6500 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; UGR ≤ 10; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination, separately controllable; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² combined ³ segment
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

