

SETA direct / indirect TW
power
suspended
074-52D9048B



Project / Type

Notes

Count / Date



| |
|-----------------------------------|
| General |
| Ceiling Suspended |
| black RAL 9005 ¹ |
| Reflector dark chrome |
| IP20 |
| indirect 6110 lm direct 3180 lm |
| total 9290 lm |

| |
|--|
| LED |
| 3000 K |
| CRI ≥ 90 |
| L90 / 50000 h |
| initial MacAdam ≤ 3 SDCM |
| R _g : 99 R _f : 91 R ₍₁₋₁₅₎ : 89 |
| MR 0.61 MDER 0.55 |

| |
|---|
| Optical |
| Reflector symmetric |
| UGR ≤ 10 ≥ 65° < 1500 cd/m ² |
| PstLM ≤ 1.0 ² SVM ≤ 0.4 ² |


| |
|---|
| Electrical |
| DALI-2 D/I separately controllable 2 DALI Addr. |
| PC1 220-240 V |
| system 93 W |
| system 100 lm/W ³ |

| |
|---|
| Physical |
| length 3063 mm width 60 mm height 60 mm |


Luminaire housing made of extruded aluminium profile; extremely slim design (only Ø 61 mm); light tight final end caps made of aluminium; no visible screws; surface black powder coated; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; spring clip attachment to the luminaire; freely positionable; incl. feed (black); extruded profile for improved thermal management; high gloss reflector with faceted design; Reflector dark chrome; direct/indirect illumination characteristic; light colour direct light component: 3000 K; light colour indirect light component: tunable white diodes (2700-6500 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; UGR ≤ 10; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 1500 cd/m²; indirect light component with integrated PC boards and high quality lens system for maximum, homogeneous ceiling illumination, separately controllable; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Light distribution



Product drawing



Installation instructions



Lighting calculator

