# **BO 32** intrack 1 lamp

180-7130538F

Project / Type

Notes

Count / Date



Tracked spotlight in die-cast aluminium with 3-phase adapter; classic style in elegant design for discerning requirements; 1 lamp; cylindrical spotlight head; surface black powder coated; spotlight head 360° rotatable and 90° tiltable; converter integrated in the power track adapter; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 37° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; adapter for toolless insertion or movement on a variety of 3-phase power tracks; adapter flush with the power track; incl. DALI-2 converter; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution




flood 37°

| h (m) | E0° (lx) | ø (m) |
|---|---|---|
| 1 | 2090 | 0.67 |
| 2 | 520 | 1.34 |
| 3 | 230 | 2.01 |
| 4 | 130 | 2.68 |
| 5 | 80 | 3.35 |

## Product drawing




### General

Ceiling , Track
tilt max 90°
rotation 360°
black , RAL 9005 [1]
IP20
755 lm

### LED

3000 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
$R_g$: 100 , $R_f$: 91 , $R_{f1-15}$: 88
MR 0.59
MDER 0.53

### Optical

flood
beam angle 37°

### Electrical

DALI-2
220-240 V
system 10.7 W
system 71 lm/W[2]
PC2
1 DALI Addr.

### Physical

diameter 32 mm
height 100 mm
0.29 kg

[1] RAL code
[2] incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions

## Lighting calculator

['180-7130538F'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

30.04.2025