

MOVE IT 45 set track x-large

indirect suspended
091-212413P



Project / Type

Notes

Count / Date



All-round extruded aluminium profile with 45 mm width groove; rectangular design; for suspended mounting (incl. 1500 mm cable suspension); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power track profile for take off of supply voltage and DALI signal; surface traffic white; powder coated / anodised; light insets can be installed and moved without tools by means of magnetic holders+locking (for the illumination of office workstations); degree of protection IP20; PC3; 48 V; incl. DALI-2 converter (PC1 220-240V); acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties can be installed; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General
Ceiling Track Suspended
X-LARGE
traffic white RAL 9016 ¹
black
IP20
indirect 11100 lm
total 11100 lm
optical inset 135 lm/W ²


LED
3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 R _f : 91 R _(f-15) : 89
MR 0.61 MDER 0.55

Electrical
DALI-2
PC3 48 V
fixture 92 W
optical inset 82 W


Physical
length 3102 mm width 1262 mm height 56 mm
14.5 kg
cable length 1500 mm

¹ RAL code ² incl. consideration of optical losses

Light distribution



Product drawing



Installation instructions



Lighting calculator

