

# MOVE IT 45 set track

large indirect suspended

091-212313P



Project / Type


Notes

Count / Date




All-round extruded aluminium profile with 45 mm width groove; rectangular design; for suspended mounting (incl. 1500 mm cable suspension); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power track profile for take off of supply voltage and DALI signal; surface traffic white; powder coated / anodised; light insets can be installed and moved without tools by means of magnetic holders+locking (for the illumination of office workstations); degree of protection IP20; PC3; 48 V; incl. DALI-2 converter (PC1 220-240V); acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties can be installed; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling | Track Suspended

LARGE

traffic white | RAL 9016 <sup>1</sup>

black

IP20

indirect 9840 lm

total 9840 lm

optical inset 135 lm/W <sup>2</sup>

## LED

3000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>(f-15)</sub>: 89

MR 0.61 | MDER 0.55

## Electrical

DALI-2

PC3 | 48 V

fixture 81 W

optical inset 73 W

## Physical

length 2482 mm | width 1262 mm | height 56 mm

12.7 kg

cable length 1500 mm

<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

## Installation instructions



## Lighting calculator

