

# MOVE IT 45 set track

medium indirect suspended


091-2122138



Project / Type

Notes

Count / Date



### General

Ceiling | Track Suspended

MEDIUM

jet black | RAL 9005 <sup>1</sup>

IP20

indirect 7510 lm

total 7510 lm

optical inset 135 lm/W <sup>2</sup>

### LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 99 | R<sub>r</sub>: 91 | R<sub>t(1-15)</sub>: 89

MR 0.61 | MDER 0.55

### Electrical

DALI-2

PC3 | 48 V

fixture 63 W

optical inset 56 W

### Physical

length 1882 mm | width 1262 mm | height 56 mm


11.1 kg

cable length 1500 mm


<sup>1</sup> RAL code <sup>2</sup> incl. consideration of optical losses

All-round extruded aluminium profile with 45 mm width groove; rectangular design; for suspended mounting (incl. 1500 mm cable suspension); height adjustment without tools; with indirect light component for additional accentuation of the ceiling; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised jet black; light insets can be installed and moved without tools by means of magnetic holders+locking (for the illumination of office workstations); degree of protection IP20; PC3; 48 V; incl. DALI-2 converter (PC1 220-240V); acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties can be installed; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



### Installation instructions



### Lighting calculator

