

MOVE IT 45 set track

medium suspended
091-2112138



Project / Type

Notes

Count / Date



General

Ceiling , Track Suspended

MEDIUM

black , RAL 9005 ¹

IP20

Electrical

DALI-2

48 V

PC3

Physical

length 1882 mm

width 1262 mm

height 56 mm

11.1 kg

cable length 1500 mm


¹ RAL code

Installation instructions



All-round extruded aluminium profile with 45 mm width groove; rectangular design; for suspended mounting (incl. 1500 mm cable suspension); height adjustment without tools; with integrated power track profile for take off of supply voltage and DALI signal; surface anodised black; light insets can be installed and moved without tools by means of magnetic holders+locking (for the illumination of office workstations); degree of protection IP20; PC3; 48 V; incl. DALI-2 converter (PC1 220-240V); acoustic element made of high quality, self-supporting, recycled PET felt with sound absorbing properties can be installed; control gear replaceable by an authorized professional;

Product drawing



[‘091-2112138’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com