

MICROPRISMATIC UGR < 19

MOVE IT PRO


086-6250930 086-6050000P



Project / Type


Notes

Count / Date



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; completely homogeneously illuminated, microprismatic PMMA cover; UGR ≤ 19; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling | Track

IP20

1990 lm

662 lm/m

LED

2700 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 101 | R_r: 90 | R_{1-15}: 88

MR 0.51 | MDER 0.46

Optical

Microprismatic | microprismatic

UGR ≤ 19 | ≥65° <3000 cd/m²

PstLM ≤ 1.0 ¹ | SVM ≤ 0.4 ¹

Electrical

DALI-2 | 1 DALI Addr.

PC2 | 220-240 V

system 20.3 W

system 98 lm/W ²

7 W/m

Physical

length 3000 mm | width 43 mm | height 13 mm

¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Lighting calculator



MICROPRISMATIC UGR

< 19

MOVE IT PRO

086-6250930 086-6050000P



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|--------|--------|--------|--------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.92 | 0.9 |
| LSF | 1 | 1 | 1 | 1 | 1 |

| | | | |
|------------------|------------------------------|-------------------|---------------------------------|
| MF | LMF × RSMF × LLMF × LSF | RSMF ^a | Room Surface Maintenance Factor |
| MF | Maintenance Factor | LLMF | Lamp Lumens Maintenance Factor |
| LMF ^a | Luminaire Maintenance Factor | LSF | Lamp Survival Factor |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 17 |
| B13 | 22 |
| B16 | 28 |
| C10 | 22 |
| C13 | 27 |
| C16 | 35 |

Components

MICROPRISMATIC COVER

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 2998-43-5 | 086-6050000P |



Mounting accessories

END CAPS

| TYPE | COLOUR | ARTICLE NUMBER(S) |
|------------------------------------|---------------|-------------------|
| 1 pair for opal and microprismatic | traffic white | 086-6091117 |
| 1 pair for opal and microprismatic | jet black | 086-6091118 |



Optical accessories

CONTINUOUS MICROPRISMATIC COVER

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 6000-43-5 | 086-6080600P |
| 25000-43-5 | 086-6082500P |

