

MICROPRISMATIC UGR

< 22

MOVE IT PRO

086-6140430 086-6040000P



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Track _____

IP20 _____

4270 lm _____

1710 lm/m _____

LED

2700 K _____

CRI \geq 80 _____

L90 / 50000 h _____

initial MacAdam \leq 3 SDCM _____

MR 0.48 | MDER 0.44 _____

Optical

Microprismatic | microprismatic _____

PstLM \leq 1.0 ¹ | SVM \leq 0.4 ¹ _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC2 | 220-240 V _____

system 41 W _____

system 104 lm/W ² _____


16 W/m _____

Physical

length 2500 mm | width 43 mm | height 13 mm _____

Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; completely homogeneously illuminated, microprismatic PMMA cover; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Lighting calculator

