

MICROPRISMATIC UGR < 22

MOVE IT PRO

086-6120030 086-6020000P



Project / Type _____

Notes _____

Count / Date _____



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; completely homogeneously illuminated, microprismatic PMMA cover; passive cooling of the LEDs through improved heat sink geometry; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;



General

Ceiling | Track _____

IP20 _____

2210 lm _____

1470 lm/m _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 | R_f: 91 | R₍₁₋₁₅₎: 89 _____

MR 0.61 | MDER 0.55 _____

Optical

Microprismatic | microprismatic _____

PstLM ≤ 1.0 ¹ | SVM ≤ 0.4 ¹ _____

Electrical

DALI-2 | 1 DALI Addr. _____

PC2 | 220-240 V _____

system 26.4 W _____

system 84 lm/W² _____


18 W/m _____

Physical

length 1500 mm | width 43 mm | height 13 mm _____

0.73 kg _____

Light distribution



Product drawing



¹ Value of containing product at full load (undimmed)
² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Lighting calculator



MICROPRISMATIC UGR < 22

MOVE IT PRO
086-6120030 086-6020000P



Project / Type _____

Notes _____

Count / Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.92	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	17
B13	22
B16	28
C10	22
C13	27
C16	35

Components

MICROPRISMATIC COVER

L-W-H (MM)	ARTICLE NUMBER(S)
1499-43-5	086-6020000P



Mounting accessories

END CAPS

TYPE	COLOUR	ARTICLE NUMBER(S)
1 pair for opal and microprismatic	traffic white	086-6091117
1 pair for opal and microprismatic	jet black	086-6091118



Optical accessories

CONTINUOUS MICROPRISMATIC COVER

L-W-H (MM)	ARTICLE NUMBER(S)
6000-43-5	086-6080600P
25000-43-5	086-6082500P

