

# MICROPRISMATIC UGR

## < 22

MOVE IT PRO

086-6110230 086-6010000P



Project / Type

Notes

Count / Date



### General

Ceiling | Track

IP20

1470 lm

1470 lm/m

### LED

3500 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 96 | R<sub>f</sub>: 90 | R<sub>f[1-5]</sub>: 91

MR 0.74 | MDER 0.67

### Optical

Microprismatic | microprismatic

PstLM ≤ 1.0<sup>1</sup> | SVM ≤ 0.4<sup>1</sup>

### Electrical

DALI-2 | 1 DALI Addr.

PC2 | 220-240 V

system 18.2 W

system 81 lm/W<sup>2</sup>


18 W/m

### Physical

length 1000 mm | width 43 mm | height 13 mm

Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; completely homogeneously illuminated, microprismatic PMMA cover; passive cooling of the LEDs through improved heat sink geometry; light colour 3500 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

### Light distribution



### Product drawing



<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Lighting calculator

