

# JUST 55

MOVE IT 25 / 25 S / 45  
050-0143938F



Project / Type


Notes

Count / Date



Cylindrical spotlight in aluminium; surface jet black powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; including high quality aluminium reflector with spherical reflector; high gloss anodised; neutral colour reflection through absolute freedom from interference colour; for brilliant object staging; precise radiation characteristic with 38° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;


## Light distribution



flood 38°

h (m)	E0° (lx)	ø (m)
1	2990	0.69
2	750	1.38
3	330	2.06
4	190	2.75
5	120	3.44

## Product drawing



### General

Ceiling | Track

tilt max 90°

rotation 360°

jet black | RAL 9005

IP20

1200 lm

### LED

2700 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 97 | R<sub>f</sub>: 91 | R<sub>(1-15)</sub>: 87

MR 0.52 | MDER 0.47

### Optical

flood | beam angle 38°

PstLM  $\leq 1.0$ <sup>1 2 3 4</sup> | SVM  $\leq 0.4$ <sup>1 2 3 4</sup>

### Electrical

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 12.7 W

fixture 94 lm/W<sup>5</sup>

### Physical

diameter 55 mm | height 100 mm

0.3 kg

<sup>1</sup> wallwasher lens BO 55 007-1965790  
<sup>2</sup> soft lens BO 55 007-1965990 <sup>3</sup> oval lens BO 55 007-1965890  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Lighting calculator

