

JUST 32 FOCUS

MOVE IT 25

050-0111038



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

black , RAL 9005 ¹

IP20

332²-411³ lm

optical inset 80²-99³ lm/W⁴

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 90 , R_{t(1-5)}: 87

MR 0.6

MDER 0.54

Optical

focus

beam angle 17°²-43°³

PstLM ≤ 1.0² ³ ⁵

SVM ≤ 0.4² ³ ⁵

Electrical

DALI-2 single control

48 V

fixture 5.5 W

optical inset 4.2 W

PC3

1 DALI Addr.

Physical

diameter 32 mm

height 73 mm


0.2 kg

¹ RAL code ² beam angle min ³ beam angle max

⁴ incl. consideration of optical losses


⁵ Value of containing product at full load (undimmed)

Light distribution



focus 43°


h (m)	E0° (lx)	ø (m)
1	740	0.80
2	185	1.59
3	82	2.39
4	46	3.18
5	30	3.98



focus 17°

h (m)	E0° (lx)	ø (m)
1	2570	0.30
2	640	0.59
3	290	0.89
4	160	1.19
5	100	1.49

Product drawing



Installation instructions



[050-0111038] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

30.04.2025