

JUST 32 FOCUS

MOVE IT 25


050-011101X



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

special colours

IP20

332¹-411² lm

optical inset 80¹-99² lm/W³

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 99 , R_r: 90 , R_{t(1-5)}: 87

MR 0.6

MDER 0.54

Optical

focus

beam angle 17°¹-43°²

P_{stLM} ≤ 1.0^{1 2 4}

SVM ≤ 0.4^{1 2 4}

Electrical

non DIM

48 V

fixture 5.5 W

optical inset 4.2 W

PC3

Physical

diameter 32 mm

height 73 mm


0.2 kg

¹ beam angle min ² beam angle max

³ incl. consideration of optical losses

⁴ Value of containing product at full load (undimmed)

Light distribution




focus 43°

h (m)	E0° (lx)	ø (m)
1	740	0.80
2	185	1.59
3	82	2.39
4	46	3.18
5	30	3.98

focus 17°

h (m)	E0° (lx)	ø (m)
1	2570	0.30
2	640	0.59
3	290	0.89
4	160	1.19
5	100	1.49

Product drawing



Installation instructions

