

# JUST 45 MOVE IT 25 / 25 S / 45

050-0131138M



Project / Type

Notes

Count / Date



Cylindrical spotlight in aluminium; surface black powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam  $\leq 2$  SDCM; CRI  $\geq 90$ ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality lens system; precise radiation characteristic with 23° beam; degree of protection IP20; PC3; 48 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); optical attachment available as accessory; accessories are listed separately; light source not replaceable;



### General

Ceiling | Track

tilt max 90°

rotation 360°

black | RAL 9005 <sup>1</sup>

IP20

947 lm

### LED

4000 K

CRI  $\geq 90$

L80 / 50000 h

initial MacAdam  $\leq 2$  SDCM

R<sub>g</sub>: 98 | R<sub>f</sub>: 90 | R<sub>t(1-15)</sub>: 88

MR 0.8 | MDER 0.72

### Optical

medium | beam angle 23°

PstLM  $\leq 1.0$ <sup>2 3 4 5</sup> | SVM  $\leq 0.4$ <sup>2 3 4 5</sup>

### Electrical

DALI-2 | 1 DALI Addr.

PC3 | 48 V

fixture 10.9 W


fixture 87 lm/W <sup>6</sup>

### Physical

diameter 45 mm | height 68 mm

0.2 kg


### Light distribution



medium 23°

h (m)	E0° (lx)	ø (m)
1	4770	0.40
2	1190	0.81
3	530	1.21
4	300	1.62
5	190	2.02

### Product drawing



<sup>1</sup> RAL code <sup>2</sup> oval lens BO 45 007-1965880  
<sup>3</sup> wallwasher lens BO 45 007-1965780  
<sup>4</sup> soft lens BO 45 007-1965980  
<sup>5</sup> Value of containing product at full load (undimmed)  
<sup>6</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator



# JUST 45 MOVE IT 25 / 25

## S / 45

050-0131138M



Project / Type

Notes

Count / Date

### Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.964	0.923	0.884	0.847	0.811
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

### Optical accessories

#### HONEYCOMB LOUVER

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
jet black	42	007-1965188



### Optical accessories

#### OVAL LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965880



#### SOFT LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965980



#### WALLWASHER LENS

Ø (MM)	ARTICLE NUMBER(S)
42	007-1965780

