

JUST 32 FOCUS

MOVE IT 25
050-0111918



Project / Type

Notes

Count / Date



General

Ceiling / Wall | Track

tilt max 90°

rotation 360°

jet black | RAL 9005

IP20

320¹-396² lm

optical inset 77¹-95² lm/W ³

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 | R_r: 91 | R_{t(15)}: 87

MR 0.52 | MDER 0.47

Optical

focus | beam angle 17°¹-43°²

PstLM ≤ 1.0^{1 2 4} | SVM ≤ 0.4^{1 2 4}

Electrical

non DIM

PC3 | 48 V

fixture 5.5 W

optical inset 4.2 W


Physical

diameter 32 mm | height 73 mm

0.2 kg

Cylindrical spotlight in aluminium; surface jet black powder coated; 360° rotatable and 90° tiltable; spotlight can be installed and moved without tools by means of magnetic holders+locking; power supplied via MOVE IT system track profile; hot plug protection; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; good glare control through recessed light point level; incl. high quality plano-convex glass lens; precise object focusing through adjustable lens; adjustable beam angle of 17° - 43°; focusing by means of patented slider on the spotlight head; degree of protection IP20; PC3; 48 V; non-dimmable; optical attachment available as accessory; accessories are listed separately; light source not replaceable;

Light distribution



focus 43°			focus 17°		
h (m)	E0° (lx)	ø (m)	h (m)	E0° (lx)	ø (m)
1	713	0.80	1	2470	0.30
2	178	1.59	2	620	0.59
3	79	2.39	3	270	0.89
4	45	3.18	4	150	1.19
5	29	3.98	5	100	1.49

Product drawing



¹ beam angle min ² beam angle max
³ incl. consideration of optical losses
⁴ Value of containing product at full load (undimmed)

Installation instructions

