

JUST 32 FOCUS

MOVE IT 25

050-0111918



Project / Type

Notes

Count / Date



General

Ceiling / Wall , Track

tilt max 90°

rotation 360°

black , RAL 9005 ¹

IP20

320²-396³ lm

optical inset 77²-95³ lm/W⁴

LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R_g: 97 , R_r: 91 , R₍₁₋₁₅₎: 87

MR 0.52

MDER 0.47

Optical

focus

beam angle 17°²-43°³

P_{stLM} ≤ 1.0³ ² ⁵

SVM ≤ 0.4³ ² ⁵

Electrical

non DIM

48 V

fixture 5.5 W

optical inset 4.2 W

PC3

Physical

diameter 32 mm

height 73 mm


0.2 kg

¹ RAL code ² beam angle min ³ beam angle max

⁴ incl. consideration of optical losses


⁵ Value of containing product at full load (undimmed)

Light distribution



focus 43°


h (m)	E0° (lx)	ø (m)
1	713	0.80
2	178	1.59
3	79	2.39
4	45	3.18
5	29	3.98



focus 17°

h (m)	E0° (lx)	ø (m)
1	2470	0.30
2	620	0.59
3	270	0.89
4	150	1.19
5	100	1.49

Product drawing



Installation instructions

