

LED CONVERSION MODULE VELA / MENO / COMBO 650

007-INRD0650151 006-CORD06501P



Project / Type


Notes

Count / Date




LED conversion module; suitable for VELA round / MENO round / COMBO round; highly reflective coating for improved efficiency; attached in the luminaire housing by means of magnets; microprismatic PMMA cover; completely homogeneous illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. converter, non dimmable; plug-in terminals for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Luminaire / Track | Mounted

white

IP20

4570¹-5640² lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

MR 0.56 | MDER 0.51

Optical

Microprismatic

$\geq 65^\circ < 3000 \text{ cd/m}^2$

$\text{PstLM} \leq 1.0^1 2^3 \text{ | SVM} \leq 0.4^1 2^3$

Electrical

non DIM

PC1 | 220-240 V

system 50 W

system 91¹-113² lm/W ⁴

Physical

diameter 572 mm | height 92 mm

¹ used in black housing ² used in white housing
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

