

# TRACK 60 CONEX plug / socket

surface / suspended system  
058-4828038



Project / Type \_\_\_\_\_  
Notes \_\_\_\_\_  
Count / Date \_\_\_\_\_



## General

Ceiling , Suspended \_\_\_\_\_  
black , RAL 9005 <sup>1</sup> \_\_\_\_\_  
IP20 \_\_\_\_\_

## Electrical

DALI-2 \_\_\_\_\_  
220-240 V \_\_\_\_\_  
PC1 \_\_\_\_\_

## Physical

length 2351 mm \_\_\_\_\_  
width 60 mm \_\_\_\_\_  
height 60 mm \_\_\_\_\_  
4.5 kg \_\_\_\_\_

<sup>1</sup> RAL code

## Installation instructions



Cylindrical power track module in aluminium; for CONEX lighting system; surface black powder coated; for wall-/ceiling surface mounting or suspended mounting (1500 mm cable suspension - oblique or straight - as an accessory); easy installation using ceiling clips (available as an accessory) or with integrated toolless suspension height adjustment; freely positioned attachment to the power track; with integrated 1-phase power track (L, N, PE) + 2 DALI copper conductors; electrical connection of the power tracks via plug/socket system; connectors (L-, T- or X-shape) available as an accessory; power track connection rotatable around its own axis, which means that any spatial angle can be realized; insets, incl. high power adapter + converter can be installed flexibly and without tools; degree of protection IP20; PC1; 220-240 V; accessories are listed separately;

## Product drawing

