

048-2750217A 048-2797117 002-90766



Project / Type

Notes

Count / Date



Ceiling | Recessed

white | RAL 9016 ¹

Mounting set traffic white

IP20

1760 lm

fixture 111 lm/W²

3500 K

CRI $\geq .90$

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_q: 96 | R_f: 90 | R_{1-15}: 91

MR 0.74 | MDER 0.67

wallwasher

$$\text{PstLM} \leq 1.0$$
$$\text{PstLM} \leq 1.0^3 \mid \text{SVM} \leq 0.4^3$$

non DIM

PC2 | 22

PC2 | 220-240 V

system 18.6 W | fixture 15.8 W

36 Vf | 450 mA

trimless

length 105 mm | width 105 mm | height 96 mm


1.57 kg

length 106 mm | width 106 mm


min. ceiling thickness 2 mm | max. ceiling thickness 25 mm

recessed depth 120 mm

Light distribution



Product drawing



Lighting calculator



[048-2750217A 048-2797117 002-90766] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

20.06.2025