

# SASSO 100 round wallwasher trim soft acoustic ceiling

048-2740214A 048-2796398 002-90780



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



## General

Ceiling , Recessed  
rotation 360°  
matt silver  
Mounting set traffic black for acoustic ceilings  
IP20  
2360 lm  
fixture 100 lm/W<sup>1</sup>

## LED

3500 K  
CRI ≥ 90  
L85 / 50000 h  
initial MacAdam ≤ 3 SDCM  
R<sub>g</sub>: 96 , R<sub>r</sub>: 90 , R<sub>t(1-15)</sub>: 91  
MR 0.74  
MDER 0.67

## Optical

wallwasher

## Electrical

non DIM  
220-240 V  
system 27.8 W  
fixture 23.7 W  
36 Vf  
650 mA  
PC2

## Physical

with trim for acoustic ceiling  
diameter 114 mm  
height 96 mm  
0.74 kg

## Cutout


diameter 100 mm  
min. ceiling thickness 25 mm  
max. ceiling thickness 40 mm  
recessed depth 120 mm

<sup>1</sup> incl. consideration of optical losses & internal control unit losses

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

