

# SASSO 100 round wallwasher/floor trimless soft acoustic ceiling

048-2740117W 048-2796198 002-90780



|                |  |
|----------------|--|
| Project / Type |  |
| Notes          |  |
| Count / Date   |  |



|  |
|--|
| <b>General</b>                                   |
| Ceiling , Recessed                               |
| rotation 360°                                    |
| white , RAL 9016 <sup>1</sup>                    |
| Mounting set traffic black for acoustic ceilings |
| IP20   |
| 2820 lm  |
| fixture 131 lm/W <sup>2</sup>                    |

|  |
|--|
| <b>LED</b>   |
| 4000 K   |
| CRI ≥ 90   |
| L80 / 50000 h  |
| initial MacAdam ≤ 2 SDCM   |
| R <sub>g</sub> : 98 , R <sub>r</sub> : 90 , R <sub>t(1-5)</sub> : 88 |
| MR 0.8   |
| MDER 0.72  |

|                  |
|------------------|
| <b>Optical</b>   |
| wallwasher floor |


|                   |
|-------------------|
| <b>Electrical</b> |
| non DIM           |
| 220-240 V         |
| system 25.2 W     |
| fixture 21.5 W    |
| 36 Vf             |
| 650 mA            |
| PC2               |

|                               |
|-------------------------------|
| <b>Physical</b>               |
| trimless for acoustic ceiling |
| diameter 114 mm               |
| height 96 mm                  |
| 0.69 kg                       |


|                              |
|------------------------------|
| <b>Cutout</b>                |
| diameter 100 mm              |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 100 mm        |

Round recessed spotlight in die-cast aluminium; 1 lamp; surface white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; passive cooling of the LEDs through improved heat sink geometry; no multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; with specially computed, asymmetrical reflector for homogeneous lighting intensity; high quality reflector with micro-faceted, aluminum-vaporised surface; PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses

## Installation instructions



## Lighting calculator



# SASSO 100 round wallwasher/floor trimless soft acoustic ceiling

048-2740117W 048-2796198 002-90780



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000            | 40 000                          | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF               | 0.964                        | 0.923  | 0.884             | 0.847                           | 0.811  |
| LSF                | 1                            | 1      | 1                 | 1                               | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> | Room Surface Maintenance Factor |        |
| MF                 | Maintenance Factor           |        | LLMF              | Lamp Lumens Maintenance Factor  |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF               | Lamp Survival Factor            |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 33                 |
| B16                            | 53                 |
| B20                            | 67                 |
| B25                            | 83                 |
| C10                            | 40                 |
| C16                            | 64                 |
| C20                            | 80                 |
| C25                            | 100                |

## Components

### MOUNTING SET trimless for soft acoustic ceilings

|                                     |        |                   |
|-------------------------------------|--------|-------------------|
| COLOUR                              | Ø (MM) | ARTICLE NUMBER(S) |
| traffic black for acoustic ceilings | 114    | 048-2796198       |



### CONVERTER

|      |            |                   |
|------|------------|-------------------|
| TYPE | L-W-H (MM) | ARTICLE NUMBER(S) |
| 31 W | 143-43-30  | 002-90780         |



## Mounting accessories

### PRIMED CONCRETE MOUNTING HOUSING

|                 |             |                   |
|-----------------|-------------|-------------------|
| COLOUR          | L-W-H (MM)  | ARTICLE NUMBER(S) |
| white aluminium | 614-307-120 | 048-2695110       |



## Mounting accessories

### MOUNTING TOOL

|               |            |                   |
|---------------|------------|-------------------|
| COLOUR        | L-W-H (MM) | ARTICLE NUMBER(S) |
| traffic black | 104-104-35 | 048-2795910       |



## Optional electrical accessories

### DIN RAIL POWER SUPPLY

|       |            |                   |
|-------|------------|-------------------|
| TYPE  | L-W-H (MM) | ARTICLE NUMBER(S) |
| 160 W | 72-90-63   | 005-6520210       |



### DIN RAIL LED DRIVER

|                                |            |                   |
|--------------------------------|------------|-------------------|
| TYPE                           | L-W-H (MM) | ARTICLE NUMBER(S) |
| DALI-2   200-1050 mA   2 x 42W | 36-88-59   | 005-6121030       |



# SASSO 100 round wallwasher/floor trimless soft acoustic ceiling

048-2740117W 048-2796198 002-90780



Project / Type

Notes

Count / Date

## Optional electrical accessories

### POWER SUPPLY PREWIRED

| TYPE                        | ARTICLE NUMBER(S) |
|-----------------------------|-------------------|
| with junktion box   DALI-2  | 002-90767A        |
| with junktion box   DALI-2  | 002-90789A        |
| with junktion box   DALI-2  | 002-90776A        |
| with junktion box   non DIM | 002-90766A        |
| with junktion box   non DIM | 002-90780A        |
| with junktion box   non DIM | 002-90774A        |

## Electrical accessories

### THROUGH WIRING CONNECTION BOX

| TYPE                                     | L-W-H (MM) | ARTICLE NUMBER(S) |
|--|------------|-------------------|
| non DIM cable ø 4 – 12 mm, Linect®-Ready | 105-58-30  | 005-2531110       |
| DALI cable ø 4 – 12 mm, Linect®-Ready    | 105-58-30  | 005-2551110       |

