

SASSO 100 round adjustable

trim

048-2720119S 048-2796317 002-90766



Project / Type

Notes

Count / Date



| |
|------------------------------------|
| General |
| Ceiling Recessed |
| tilt max 30° |
| rotation 360° |
| gold dust RAL 260-M ¹ |
| Mounting set traffic white |
| front IP40 back IP20 |
| 1750 lm |
| fixture 115 lm/W ² |

| |
|----------------------------------------------------------------------|
| LED |
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 98 R _f : 90 R _[1-15] : 88 |
| MR 0.8 MDER 0.72 |

| |
|---------------------------------------------------|
| Optical |
| spot beam angle 20° |
| UGR ≤ 10 |
| PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³ |


| |
|--------------------------------|
| Electrical |
| non DIM |
| PC2 220-240 V |
| system 17.9 W fixture 15.2 W |
| 36 Vf 450 mA |

| |
|--------------------------------|
| Physical |
| trim |
| diameter 118 mm height 95 mm |
| 1.31 kg |

| |
|------------------------------------------------------------|
| Cutout |
| diameter 108 mm |
| min. ceiling thickness 2 mm max. ceiling thickness 25 mm |
| recessed depth 100 mm |

Round recessed spotlight in die-cast aluminium; 1 lamp; surface gold dust; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 20° beam; UGR ≤ 10; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

