

# SASSO 100 round downlight trim soft acoustic ceiling

048-2700911M 048-2796397 002-90766



Project / Type

Notes

Count / Date



## General

Ceiling , Recessed  
black , RAL 9005 <sup>1</sup>  
Mounting set signal white for acoustic ceilings  
front IP44 , back IP20  
1620 lm  
fixture 107 lm/W<sup>2</sup>

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 97 , R<sub>f</sub>: 91 , R<sub>(1-15)</sub>: 87  
MR 0.52  
MDER 0.47

## Optical

medium  
beam angle 31°  
UGR ≤ 13 , ≥65° <3000 cd/m<sup>2</sup>  
PstLM ≤ 1.0 <sup>3</sup>  
SVM ≤ 0.4 <sup>3</sup>

## Electrical

non DIM  
220-240 V  
system 17.9 W  
fixture 15.2 W  
36 Vf  
450 mA  
PC2

## Physical

with trim for acoustic ceiling  
diameter 114 mm  
height 75 mm  
1.39 kg

## Cutout


diameter 100 mm  
min. ceiling thickness 25 mm  
max. ceiling thickness 40 mm  
recessed depth 80 mm

<sup>1</sup> RAL code


<sup>2</sup> incl. consideration of optical losses & internal control unit losses

<sup>3</sup> Value of containing product at full load (undimmed)

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

