

SASSO 100 round downlight

trimless

048-2700117F 048-2796117 002-90766



Project / Type


Notes

Count / Date




Round recessed spotlight in die-cast aluminium; 1 lamp; surface white; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in plasterboard ceilings; suitable for ceiling thickness of 12.5/15/25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; UGR ≤ 19 ; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

| |
|-------------------------------|
| Ceiling Recessed |
| white RAL 9016 ¹ |
| Mounting set traffic white |
| front IP44 back IP20 |
| 1790 lm |
| fixture 118 lm/W ² |

LED

| |
|---|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 98 R _f : 90 R _{t(1-15)} : 88 |
| MR 0.8 MDER 0.72 |

Optical

| |
|---|
| flood beam angle 39° |
| UGR ≤ 19 |
| PstLM ≤ 1.0 ³ SVM ≤ 0.4 ³ |

Electrical

| |
|--------------------------------|
| non DIM |
| PC2 220-240 V |
| system 17.9 W fixture 15.2 W |
| 36 Vf 450 mA |

Physical

| |
|--------------------------------|
| trimless |
| diameter 105 mm height 75 mm |
| 1.33 kg |

Cutout

| |
|---|
| diameter 106 mm |
| min. ceiling thickness 12.5 mm max. ceiling thickness 25 mm |
| recessed depth 80 mm |

¹ RAL code
² incl. consideration of optical losses & internal control unit losses
³ Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

