

SASSO 100 round downlight trimless soft acoustic ceiling

048-2700014M 048-2796197 002-90780



Project / Type

Notes

Count / Date



IP20

IP44

| |
|---|
| General |
| Ceiling , Recessed |
| matt silver |
| Mounting set signal white for acoustic ceilings |
| front IP44 , back IP20 |
| 2060 lm |
| fixture 91 lm/W ¹ |

| |
|--|
| LED |
| 3000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| initial MacAdam ≤ 2 SDCM |
| R _g : 99 , R _f : 90 , R ₍₁₋₁₅₎ : 87 |
| MR 0.6 |
| MDER 0.54 |

| |
|---|
| Optical |
| medium |
| beam angle 33° |
| UGR ≤ 16 , ≥65° <3000 cd/m ² |


| |
|----------------|
| Electrical |
| non DIM |
| 220-240 V |
| system 26.7 W |
| fixture 22.7 W |
| 36 Vf |
| 650 mA |
| PC2 |

| |
|-------------------------------|
| Physical |
| trimless for acoustic ceiling |
| diameter 114 mm |
| height 75 mm |
| 0.54 kg |


| |
|------------------------------|
| Cutout |
| diameter 100 mm |
| min. ceiling thickness 25 mm |
| max. ceiling thickness 40 mm |
| recessed depth 80 mm |

¹ incl. consideration of optical losses & internal control unit losses

Light distribution



Product drawing



Installation instructions



Lighting calculator

