

SASSO 60 emergency light pro trim soft acoustic ceiling

048-2693237 048-2696397



Project / Type _____
 Notes _____
 Count / Date _____



General

Ceiling | Recessed
 rotation 360°
 traffic white | RAL 9016 ¹
 Mounting set traffic white
 IP20
 206², 208³, 217⁴ lm

LED

6500 K
 CRI ≥ 80

Optical

emergency light | beam angle 21°², 103°x25°³, 149°x150°⁴

Electrical

PC2 | 220-240 V
 system 1.0 W
 system 206², 208³, 217⁴ lm/W ⁵

Physical


with trim for acoustic ceiling
 diameter 80 mm | height 94 mm
 0.34 kg

Cutout


diameter 74 mm
 min. ceiling thickness 25 mm | max. ceiling thickness 40 mm
 recessed depth 110 mm

Round LED emergency light inset; surface lacquered in traffic white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim traffic white; for installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; Pro DALI with monitoring via DALI; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2; light source not replaceable;

Light distribution



Product drawing



¹ RAL code ² Spot lens ³ Escape route lens ⁴ Anti panic lens
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator



SASSO 60 emergency light pro trim soft acoustic ceiling

048-2693237 048-2696397



Project / Type _____

Notes _____

Count / Date _____

Components

MOUNTING SET trim for soft acoustic ceilings

COLOUR	Ø (MM)	ARTICLE NUMBER(S)
traffic white	80	048-2696397



Mounting accessories

MOUNTING TOOL

COLOUR	L-W-H (MM)	ARTICLE NUMBER(S)
traffic black	77-77-35	048-2695918



Electrical accessories

REPLACEMENT ACCUPACK

TYPE	ARTICLE NUMBER(S)
3h battery life	048-2693910

