

# SASSO 60 emergency light

## pro trimless soft acoustic ceiling

048-2693237 048-2696198



Project / Type
Notes
Count / Date



### General

Ceiling , Recessed
rotation 360°
white , RAL 9016 <sup>1</sup>
Mounting set traffic black for acoustic ceilings
IP20
206 <sup>2</sup> , 208 <sup>3</sup> , 217 <sup>4</sup> lm

### LED

6500 K
CRI ≥ 80

### Optical

emergency light
beam angle 21° <sup>2</sup> , 103°x25° <sup>3</sup> , 149°x150° <sup>4</sup>

### Electrical

220-240 V
system 1.0 W
system 206 <sup>2</sup> , 208 <sup>3</sup> , 217 <sup>4</sup> lm/W <sup>5</sup>
PC2

### Physical


trimless for acoustic ceiling
diameter 80 mm
height 94 mm
0.39 kg

Round LED emergency light inset; surface lacquered in white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; traffic black for acoustic ceilings; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; Pro DALI with monitoring via DALI; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2; light source not replaceable;

### Light distribution



### Product drawing



### Cutout

diameter 74 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Spot lens <sup>3</sup> Escape route lens <sup>4</sup> Anti panic lens  
<sup>5</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator



[‘048-2693237 048-2696198’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · [www.xal.com](http://www.xal.com)

01.05.2025