

# SASSO 60 emergency light selftest trimless soft acoustic ceiling

048-2693227 048-2696198



Project / Type

Notes

Count / Date




Round LED emergency light inset; surface lacquered in white; 360° rotatable; installation without tools in mounting set due to patented ball catch system; round installation housing; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; incl. 3 interchangeable lenses: anti panic / escape route / spot; incl. 3h rechargeable battery; selftest with status LED; light colour 6500 K; CRI ≥ 80; degree of protection IP20; PC2; light source not replaceable;

## Light distribution



## Product drawing



### General

Ceiling | Recessed

rotation 360°

white | RAL 9016 <sup>1</sup>

IP20

206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm

### LED

6500 K

CRI ≥ 80

### Optical

emergency light | beam angle 21°<sup>2</sup>, 103°x25°<sup>3</sup>, 149°x150°<sup>4</sup>

### Electrical

PC2 | 220-240 V

system 1.0 W

system 206<sup>2</sup>, 208<sup>3</sup>, 217<sup>4</sup> lm/W <sup>5</sup>

### Physical

trimless for acoustic ceiling

diameter 80 mm | height 94 mm

0.45 kg

### Cutout

diameter 74-76 mm

min. ceiling thickness 25 mm | max. ceiling thickness 40 mm

recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Spot lens <sup>3</sup> Escape route lens <sup>4</sup> Anti panic lens  
<sup>5</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Lighting calculator

