

# SASSO 60 sensor sense trimless soft acoustic ceiling

048-2693121 048-2696198



Project / Type

Notes

Count / Date



General

Ceiling | Recessed

rotation 360°

black | RAL 9005 <sup>1</sup>

front IP40 | back IP20

Electrical

DALI-2 SENSE sensor | 1 DALI Addr.

brightness, presence, temperature, sound  
pressure, air quality, humidity

PC2 | 220-240 V

Physical

trimless for acoustic ceiling

diameter 80 mm | height 40 mm

0.24 kg

Cutout

diameter 74-76 mm


min. ceiling thickness 25 mm | max. ceiling  
thickness 40 mm

recessed depth 60 mm

Round sensor inset; SENSE (brightness, presence, temperature, humidity, air quality and noise level sensor); surface lacquered in black; 360° rotatable; installation without tools with mounting kit; round installation housing; for trimless installation in soft acoustic ceilings; suitable for ceiling thickness of 25-40 mm; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; DALI-2 control;

<sup>1</sup> RAL code

Product drawing



Installation  
instructions



# SASSO 60 sensor sense trimless soft acoustic ceiling

048-2693121 048-2696198



Project / Type

Notes

Count / Date

### Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	48
B13	62
B16	77
B20	96
C10	48
C13	62
C16	77
C20	96

### Mounting accessories

#### MOUNTING TOOL

COLOUR	L·W·H (MM)	ARTICLE NUMBER(S)
traffic black	77·77·35	048-2695918



### Electrical accessories

#### REPLACEMENT ACCUPACK

TYPE	ARTICLE NUMBER(S)
3h battery life	048-2693910

