

048-2602E19F 048-2696197 002-90762



Project / Type

## Notes

Count / Date



Ceiling, Recessed  
rotation 360°  
gold, RAL 260-M<sup>1</sup>  
Mounting set signal white for acoustic ceilings  
front IP40, back IP20  
714 lm  
fixture 70 lm/W<sup>2</sup>

colour warm dimming
1800 K - 3000 K
CRI $\geq$ 90
L85 / 50000 h
initial MacAdam $\leq$ 3 SDCM
R <sub>g</sub> : 101, R <sub>f</sub> : 94, R <sub>{f-15}</sub> : 97
MR 0.64
MDR 0.58

flood
beam angle 36°
UGR ≤ 19
PstLM ≤ 1.0 <sup>3</sup>
SVM ≤ 0.4 <sup>3</sup>


DALI-2
220-240 V
system 12.0 W
fixture 10.2 W
300 mA
PC2
1 DALI Addr.

trimless for acoustic ceiling
diameter 80 mm
height 48 mm
0.66 kg

diameter 74 mm
min. ceiling thickness 25 mm
max. ceiling thickness 40 mm
recessed depth 120 mm

<sup>1</sup> RAL code<sup>2</sup> incl. consideration of optical losses & internal control unit losses<sup>3</sup> Value of containing product at full load (undimmed)

## Light distribution



 60  
non DIM  
 120  
DALI-2  
 74  
 25  
 80

# SASSO 60 round downlight trimless soft acoustic ceiling

048-2602E19F 048-2696197 002-90762



Project / Type

Notes

Count / Date

Installation  
instructions



Lighting  
calculator

