

SASSO 100 square wallwasher

trimless

048-2750219A 048-2797117 002-90789



Project / Type

Notes

Count / Date



General

Ceiling | Recessed
gold | RAL 260-M¹
Mounting set traffic white
IP20
2290 lm
fixture 97 lm/W²

LED

3500 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R_g: 96 | R_f: 90 | R_{f(1-15)}: 91
MR 0.74 | MDER 0.67

Optical

wallwasher
PstLM ≤ 1.0³ | SVM ≤ 0.4³

Electrical

DALI-2
PC2 | 220-240 V
system 27.8 W | fixture 23.7 W
36 Vf | 650 mA

Physical

trimless
length 105 mm | width 105 mm | height 96 mm
0.83 kg

Cutout

length 106 mm | width 106 mm
min. ceiling thickness 2 mm | max. ceiling
thickness 25 mm
recessed depth 120 mm

¹ RAL code

² incl. consideration of optical losses & internal control unit losses

³ Value of containing product at full load (undimmed)


Installation instructions




Lighting calculator



Light distribution



Product drawing



[048-2750219A 048-2797117 002-90789] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

20.06.2025