

# SASSO 100 round adjustable

trimless exposed concrete

048-2720017F 048-2795210 002-90767



Project / Type

Notes

Count / Date



General	
Ceiling   Recessed	
tilt max 30°	
rotation 360°	
traffic white   RAL 9016 <sup>1</sup>	
Mounting set white aluminium	
front IP40   back IP20	
1710 lm	
fixture 113 lm/W <sup>2</sup>	

LED	
3000 K	
CRI ≥ 90	
L80 / 50000 h	
initial MacAdam ≤ 2 SDCM	
R <sub>g</sub> : 99   R <sub>f</sub> : 90   R <sub>t-15</sub> : 87	
MR 0.6   MDER 0.54	

Optical	
flood   beam angle 39°	
UGR ≤ 19	
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>	


Electrical	
DALI-2   1 DALI Addr.	
PC2   220-240 V	
system 17.9 W   fixture 15.2 W	
36 Vf   450 mA	

Physical	
trimless for exposed concrete ceiling	
length 230 mm   width 230 mm   height 162 mm	
2.61 kg	


Cutout	
recessed depth 100 mm	

Round recessed spotlight in die-cast aluminium; 1 lamp; surface traffic white; 360° rotatable and 30° tiltable; installation without tools in mounting set due to patented ball catch system; concrete housings for exposed concrete ceilings; for trimless installation; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3000 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 39° beam; UGR ≤ 19; degree of protection from below IP40 (from above IP20); PC2; 220-240 V; incl. DALI-2 converter; through wiring connection box, 3-pole or 5-pole, available as an accessory; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

### Installation instructions

### Lighting calculator