

# SASSO 40 round adjustable

trim

048-2820619F 048-2896318 002-90753



Project / Type

Notes

Count / Date



360°

220-240 V

IP20 / IP40

General	
Ceiling   Recessed	
tilt max 30°	
rotation 360°	
gold   RAL 260-M <sup>1</sup>	
Mounting set jet black	
front IP40   back IP20	
407 lm	
fixture 80 lm/W <sup>2</sup>	
LED	
4000 K	
CRI ≥ 90	
L85 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 94   R <sub>f</sub> : 87   R <sub>l-15</sub> : 90	
MR 0.86   MDER 0.78	


Optical	
flood   beam angle 46°	
UGR ≤ 19	
PstLM ≤ 1.0 <sup>3</sup>   SVM ≤ 0.4 <sup>3</sup>	

Electrical	
DALI-2	
PC2   220-240 V	
system 6.2 W   fixture 5.1 W	
12 Vf   450 mA	


Physical	
trim	
diameter 60 mm   height 50 mm	
0.59 kg	

Cutout	
diameter 56 mm	
min. ceiling thickness 2 mm   max. ceiling thickness 25 mm	
recessed depth 120 mm	

## Light distribution



## Product drawing



<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

