

SASSO 40 round downlight


trim

048-2800614M 048-2896318 002-90752



Round recessed spotlight in die-cast aluminium; surface matt silver; installation without tools in mounting set due to patented ball catch system; round installation housing; with trim jet black; suitable for ceiling thickness of 2-25 mm; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 25° beam; UGR ≤ 10 ; degree of protection from below IP44 (from above IP20); PC2; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |



General

| | |
|------------------------------|--|
| Ceiling , Recessed | |
| rotation 360° | |
| matt silver | |
| Mounting set jet black | |
| front IP44 , back IP20 | |
| 404 lm | |
| fixture 79 lm/W ¹ | |

LED

| | |
|--|--|
| 4000 K | |
| CRI ≥ 90 | |
| L85 / 50000 h | |
| initial MacAdam ≤ 3 SDCM | |
| R _g : 94 , R _r : 87 , R ₍₁₋₁₅₎ : 90 | |
| MR 0.86 | |
| MDER 0.78 | |

Optical

| | |
|-------------------------------|--|
| medium | |
| beam angle 25° | |
| UGR ≤ 10 | |
| PstLM ≤ 1.0 ² | |
| SVM ≤ 0.4 ² | |

Electrical

| | |
|---------------|--|
| non DIM | |
| 220-240 V | |
| system 6.2 W | |
| fixture 5.1 W | |
| 12 Vf | |
| 450 mA | |
| PC2 | |

Physical

| | |
|----------------|--|
| trim | |
| diameter 60 mm | |
| height 50 mm | |
| 0.21 kg | |

Cutout

| | |
|------------------------------|--|
| diameter 56 mm | |
| min. ceiling thickness 2 mm | |
| max. ceiling thickness 25 mm | |
| recessed depth 120 mm | |

¹ incl. consideration of optical losses & internal control unit losses
² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

