

# SASSO 100 round adjustable trim soft acoustic ceiling

048-2720214F 048-2796398 002-90766



Project / Type

Notes

Count / Date



360°

IP20  
IP40

X-PERT

220-240 V

### General

Ceiling | Recessed

tilt max 30°

rotation 360°

matt silver

Mounting set jet black

front IP40 | back IP20

1660 lm

fixture 109 lm/W <sup>1</sup>

### LED

3500 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 90 | R<sub>[1-15]</sub>: 89

MR 0.7 | MDER 0.64

### Optical

flood | beam angle 39°

UGR ≤ 16 | ≥65° <1500 cd/m<sup>2</sup>

PstLM ≤ 1.0 <sup>2</sup> | SVM ≤ 0.4 <sup>2</sup>

### Electrical

non DIM

PC2 | 220-240 V

system 17.9 W | fixture 15.2 W

36 Vf | 450 mA

### Physical

with trim for acoustic ceiling

diameter 114 mm | height 95 mm

1.44 kg


### Cutout

diameter 100 mm


min. ceiling thickness 25 mm | max. ceiling thickness 40 mm

recessed depth 100 mm

### Light distribution



### Product drawing



<sup>1</sup> incl. consideration of optical losses & internal control unit losses  
<sup>2</sup> Value of containing product at full load (undimmed)

### Installation instructions



### Lighting calculator

