


# LENS WIDE

MOVE IT PRO  
086-6730430W



Linear light inset made of plastic; light inset, incl. high power adapter + converter can be installed flexibly and without tools; flush with profile system; power supplied via MOVE IT PRO system track profile; equipped with specially computed wide beam lenses; precise radiation characteristic with symmetrical light distribution; for use in schools and offices; UGR  $\leq 19$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 3000 \text{ cd/m}^2$ ; passive cooling of the LEDs through improved heat sink geometry; light colour 2700 K; binning initial MacAdam  $\leq 3 \text{ SDCM}$ ; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC2; 220-240 V; DALI single control; flicker-free visual comfort through analogue current control (minimum value 1%); light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



Project / Type	
Notes	
Count / Date	



### General

Ceiling , Track
lens inset
white
IP20
5140 lm
2570 lm/m

### LED

2700 K
CRI $\geq 80$
L90 / 50000 h
initial MacAdam $\leq 3 \text{ SDCM}$
MR 0.48
MDER 0.44

### Optical

wide flood
UGR $\leq 19$ , $\geq 65^\circ < 3000 \text{ cd/m}^2$
PstLM $\leq 1.0$ <sup>1</sup>
SVM $\leq 0.4$ <sup>1</sup>

### Electrical

DALI-2
220-240 V
system 33 W
system 156 lm/W <sup>2</sup>
PC2
1 DALI Addr.
17 W/m

### Physical

length 2000 mm
width 43 mm
height 13 mm

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Installation instructions



### Lighting calculator

