

# FRAME 40 flex mid lumen

trim system

042-011G037 006-4220010Z 042-7004017



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Recessed
traffic white , RAL 9016 <sup>1</sup>
IP20
2400 lm
1200 lm/m

## LED

3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.61
MDER 0.55

## Optical

Microprismatic
microprismatic
PstLM ≤ 1.0 <sup>2</sup> <sup>3</sup>
SVM ≤ 0.4 <sup>2</sup> <sup>3</sup>

## Electrical

DALI-2
220-240 V
system 23.4 W
system 103 lm/W <sup>4</sup>
PC1
12 W/m

## Physical

trim
length 2000 mm
width 55 mm
height 60 mm
3.7 kg
L (mm): 1500 - 2000, breakable every 125mm

## Cutout


length 2010 mm
width 45 mm
min. ceiling thickness 8 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> 2000mm  
<sup>3</sup> Value of containing product at full load (undimmed)  
<sup>4</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Light distribution



## Product drawing

