

FRAME 40 flex mid lumen

trim system

042-011G037 006-4220010H 042-7004018



Project / Type


Notes

Count / Date



Luminaire housing made of extruded aluminium profile; recessed light with wrap around edge; for continuous lighting systems; suitable for ceiling thickness of 8-25 mm; surface black powder coated; luminaire profile can be pre-mounted; pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling | Recessed

black | RAL 9005 ¹

IP20

2720 lm

1360 lm/m

LED

3000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_f: 91 | R_{h-15}: 89

MR 0.61 | MDER 0.55

Optical

High Performance Opal | opal (lambertsch)

PstLM ≤ 1.0 ^{2 3 4 5 6 7} | SVM ≤ 0.4 ^{2 3 4 5 6 7}

Electrical

DALI-2

PC1 | 220-240 V

system 23.4 W

system 116 lm/W ⁸

12 W/m

Physical

trim

length 2000 mm | width 55 mm | height 60 mm

3.9 kg

L (mm): 1500 - 2000, breakable every 125mm

Cutout

length 2010 mm | width 45 mm

min. ceiling thickness 8 mm | max. ceiling thickness 25 mm

recessed depth 100 mm

¹ RAL code ² 2000mm ³ 1625mm ⁴ 1500mm ⁵ 1875mm ⁶ 1750mm
⁷ Value of containing product at full load (undimmed)
⁸ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator

