

# MINO 40 flex mid lumen

ceiling / suspended system

042-011F137 006-4210010H 042-100201W



Project / Type
Notes
Count / Date



## General

Ceiling , Suspended
RAL Traffic white , RAL 9016 <sup>1</sup>
IP20
1470 lm
1470 lm/m

## LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 92 , R <sub>t(1-15)</sub> : 90
MR 0.81
MDER 0.74

## Optical

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 <sup>2</sup> <sup>3</sup>
SVM ≤ 0.4 <sup>2</sup> <sup>3</sup>

## Electrical


DALI-2
220-240 V
system 12.1 W
system 121 lm/W <sup>4</sup>
PC1
12 W/m

## Physical

length 1000 mm
width 40 mm
height 65 mm
1.75 kg
L (mm): 500 - 1000, breakable every 62.5mm

<sup>1</sup> RAL code <sup>2</sup> 1000mm  
<sup>3</sup> Value of containing product at full load (undimmed)  
<sup>4</sup> incl. consideration of optical losses, internal control unit losses  
and operating device efficiency

## Light distribution



## Product drawing

