

MINO 40 flex mid lumen

ceiling / suspended system

042-011F137 006-4210010H 042-1002018



Project / Type
Notes
Count / Date



General

Ceiling , Suspended
black , RAL 9005 ¹
IP20
1470 lm
1470 lm/m

LED

4000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _r : 92 , R _{t(1-15)} : 90
MR 0.81
MDER 0.74

Optical

High Performance Opal
opal (lambertsch)
PstLM ≤ 1.0 ² ³
SVM ≤ 0.4 ² ³


Electrical

DALI-2
220-240 V
system 12.1 W
system 121 lm/W ⁴
PC1
12 W/m


Physical

length 1000 mm
width 40 mm
height 65 mm
1.27 kg
L (mm): 500 - 1000, breakable every 62.5mm

Light distribution



Product drawing



[‘042-011F137 006-4210010H 042-1002018’] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com