

FRAME 40 flex mid lumen

trim system

042-011F037 006-4210010Z 042-7002017



Project / Type	
Notes	
Count / Date	



General

Ceiling , Recessed
traffic white , RAL 9016 ¹
IP20
1200 lm
1200 lm/m

LED

3000 K
CRI ≥ 90
L90 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 99 , R _r : 91 , R _{t(1-15)} : 89
MR 0.61
MDER 0.55

Optical

Microprismatic
microprismatic
PstLM ≤ 1.0 ² ³
SVM ≤ 0.4 ² ³

Electrical

DALI-2
220-240 V
system 12.1 W
system 99 lm/W ⁴
PC1
12 W/m

Physical

trim
length 1000 mm
width 55 mm
height 60 mm
1.68 kg
L (mm): 500 - 1000, breakable every 62.5mm

Cutout


length 1010 mm
width 45 mm
min. ceiling thickness 8 mm
max. ceiling thickness 25 mm
recessed depth 100 mm

¹ RAL code ² 1000mm
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Installation instructions



Light distribution



Product drawing

