

FRAME 40 flex mid lumen

trim system

042-011F037 006-4210010H 042-7002018



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Recessed _____

black , RAL 9005 ¹ _____

IP20 _____

1360 lm _____

1360 lm/m _____

LED

3000 K _____

CRI ≥ 90 _____

L90 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.61 _____

MDER 0.55 _____

Optical

High Performance Opal _____

opal (lambertsch) _____

PstLM ≤ 1.0² ³ _____

SVM ≤ 0.4² ³ _____

Electrical

DALI-2 _____

220-240 V _____

system 12.1 W _____

system 112 lm/W⁴ _____

PC1 _____

12 W/m _____

Physical

trim _____

length 1000 mm _____

width 55 mm _____

height 60 mm _____

0.7 kg _____

L (mm): 500 - 1000, breakable every 62.5mm _____

Cutout

length 1010 mm _____

width 45 mm _____

min. ceiling thickness 8 mm _____

max. ceiling thickness 25 mm _____

recessed depth 100 mm _____

¹ RAL code ² 1000mm


³ Value of containing product at full load (undimmed)

⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Light distribution



Product drawing

