

# FRAME 40 high lumen

trim system

042-0124037 006-4220010Z 042-700401G



Project / Type


Notes

Count / Date




Luminaire housing made of extruded aluminium profile; recessed light with wrap around edge; for continuous lighting systems; suitable for ceiling thickness of 8-25 mm; surface grey powder coated; luminaire profile can be pre-mounted; pre-assembled power rail for power supply in luminaire profile; voltage tap of the light inset on the power rail; remaining lamp components mounted without tools; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



## General

Ceiling | Recessed

grey | RAL 9006 <sup>1</sup>

IP20

3700 lm

1850 lm/m

## LED

3000 K

CRI  $\geq 90$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 91 | R<sub>f(1-15)</sub>: 89

MR 0.61 | MDER 0.55

## Optical

Microprismatic | microprismatic

PstLM  $\leq 1.0$  <sup>2</sup> | SVM  $\leq 0.4$  <sup>2</sup>

## Electrical

DALI-2

PC1 | 220-240 V

system 36 W

system 103 lm/W <sup>3</sup>

18 W/m

## Physical

trim

length 2000 mm | width 55 mm | height 60 mm

3.7 kg

## Cutout

length 2010 mm | width 45 mm

min. ceiling thickness 8 mm | max. ceiling thickness 25 mm

recessed depth 100 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses and operating device efficiency

## Installation instructions



## Lighting calculator



# FRAME 40 high lumen

trim system

042-0124037 006-4220010Z 042-700401G



Project / Type

Notes

Count / Date

## Maintenance Factors

| Operating Time [h] | 10 000                       | 20 000 | 30 000            | 40 000                          | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF               | 0.98                         | 0.96   | 0.94              | 0.92                            | 0.9    |
| LSF                | 1                            | 1      | 1                 | 1                               | 1      |
| MF                 | LMF × RSMF × LLMF × LSF      |        | RSMF <sup>a</sup> | Room Surface Maintenance Factor |        |
| MF                 | Maintenance Factor           |        | LLMF              | Lamp Lumens Maintenance Factor  |        |
| LMF <sup>a</sup>   | Luminaire Maintenance Factor |        | LSF               | Lamp Survival Factor            |        |

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10                            | 13                 |
| B13                            | 17                 |
| B16                            | 21                 |
| B20                            | 27                 |
| C10                            | 21                 |
| C13                            | 28                 |
| C16                            | 35                 |
| C20                            | 45                 |

## Components

### LINEAR COVER

|                   |
|-------------------|
| ARTICLE NUMBER(S) |
| 006-4220010Z      |

### INSTALLATION CHANNEL with trim

|                 |            |                   |
|-----------------|------------|-------------------|
| COLOUR          | L-W-H (MM) | ARTICLE NUMBER(S) |
| white aluminium | 2000-55-60 | 042-700401G       |

## Mounting accessories

### END CAPS recessed trim

|        |                 |            |                   |
|--------|-----------------|------------|-------------------|
| TYPE   | COLOUR          | L-W-H (MM) | ARTICLE NUMBER(S) |
| 1 pair | traffic white   | 55-60-8    | 042-7090017       |
| 1 pair | white aluminium | 55-60-8    | 042-709001G       |
| 1 pair | jet black       | 55-60-8    | 042-7090018       |

## Mounting accessories

### LINEAR CONNECTOR

|                         |           |            |                   |
|-------------------------|-----------|------------|-------------------|
| TYPE                    | COLOUR    | L-W-H (MM) | ARTICLE NUMBER(S) |
| mechanical              | jet black | 120-36-14  | 042-7091110       |
| mechanical & electrical | jet black | 120-36-14  | 042-7091230       |

### OPAL COVER LINEAR CONNECTOR

|            |            |                   |
|------------|------------|-------------------|
| COLOUR     | L-W-H (MM) | ARTICLE NUMBER(S) |
| pure white | 120-36-14  | 042-1091910       |

### MICROPRISMATIC COVER LINEAR CONNECTOR

|            |            |                   |
|------------|------------|-------------------|
| COLOUR     | L-W-H (MM) | ARTICLE NUMBER(S) |
| pure white | 120-36-14  | 042-1091810       |





Project / Type

Notes

Count / Date

Mounting accessories

MOUNTING BRACKET recessed trim

| TYPE      | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece   | 042-7092110       |
| 25 pieces | 042-7092110.25    |



Electrical accessories

POWER FEEDER UNIT

| L-W-H (MM) | ARTICLE NUMBER(S) |
|------------|-------------------|
| 80-36-17   | 042-1093230       |



Optical accessories

BLIND COVER

| COLOUR          | ARTICLE NUMBER(S) |
|-----------------|-------------------|
| traffic white   | 006-4210017B      |
| jet black       | 006-4210018B      |
| white aluminium | 006-421001GB      |
| traffic white   | 006-4220017B      |
| jet black       | 006-4220018B      |
| white aluminium | 006-422001GB      |
| traffic white   | 006-4230017B      |
| jet black       | 006-4230018B      |
| white aluminium | 006-423001GB      |



CONTINUOUS LINEAR COVER

| ARTICLE NUMBER(S) |
|-------------------|
| 006-2225010H      |
| 006-2206010H      |

