

SASSO 100 round

wall


EN Cylindrical wall surface mounted luminaire made of aluminium; light inset lacquered; surface housing powder coated; optionally symmetric direct or direct / indirect light distribution; homogeneous wall or ceiling illumination through uniform light distribution; precise radiation characteristic due to high quality lens system; installation of variant DIRECT optionally for floor or ceiling illumination; COB (Chip on Board) technology for maximum efficiency; no multiple shadows; efficient LEDs with very good colour rendering

DE Zylindrische Wandanbauleuchte aus Aluminium; Lichteinsatz lackiert; Oberfläche Gehäuse pulverbeschichtet; wahlweise symmetrisch direkte oder direkt/indirekte Abstrahlcharakteristik; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige Lichtverteilung; präzise Abstrahlcharakteristik durch hochwertige Linsenoptik; Montage Variante DIRECT wahlweise zur Boden- oder Deckenaufhellung; COB (Chip on Board) Technologie für höchste Effizienz; keine Mehrfachschatten; effiziente LEDs mit sehr guter Farbwiedergabe

Quickinfo

2700 K, 3000 K, 3500 K, 4000 K
CRI $\geq$ 90 / 2 SDCM
up to $\downarrow$ 1,200 lm / $\uparrow$ 1,200 lm
up to 67 lm/W
L80 / 50000 h
DALI-2, non DIM
IP20

Types



Colour



Inner colour



Light distributions



direct and
direct / indirect
illumination




high quality
lens



easy mounting



CRI $\geq$ 95 2
SDCM
(optional)




SASSO 100 round direct wall



OPAL LENS | DIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
17.9 W	2700 K	1110 lm	62 lm/W	0 4 8 - 3 4 5 0 9 O
	3000 K	1150 lm	64 lm/W	0 4 8 - 3 4 5 0 0 O
	3500 K	1170 lm	65 lm/W	0 4 8 - 3 4 5 0 2 O
	4000 K	1200 lm	67 lm/W	0 4 8 - 3 4 5 0 1 O



SASSO 100 round direct / indirect wall



OPAL LENS | DIRECT / INDIRECT CRI ≥ 90

SYSTEM	COLOUR TEMP.	LUM. FLUX	SYSTEM	ORDER CODE
36.0 W	2700 K	↓1110/↑1110 lm	62 lm/W	0 4 8 - 3 4 6 0 9 O
	3000 K	↓1150/↑1150 lm	64 lm/W	0 4 8 - 3 4 6 0 0 O
	3500 K	↓1170/↑1170 lm	65 lm/W	0 4 8 - 3 4 6 0 2 O
	4000 K	↓1200/↑1200 lm	67 lm/W	0 4 8 - 3 4 6 0 1 O

Optical accessories (optional)



HONEYCOMB LOUVER

TYPE	COLOUR	Ø-H (mm)	ORDER CODE
for BO 55 SASSO 100	jet black	50-3	0 0 7 - 1 9 6 5 5 9 8

Order options

CONTROL		COLOUR		INNER COLOUR	
non DIM	1	jet black RAL 9005	1	jet black	1
DALI-2	3	traffic white RAL 9016	7	matt silver	4
				traffic white	7
				gold dust	9

MAM Competence Center, Großhöflein

Austria

Architect

INNOCAD Architektur
ZT

Lighting Design

INNOCAD Architektur
ZT

Photographer

Paul Ott



Used products



**TASK round
suspended**



LITO 60 suspended



SONIC free standing



**SASSO 100 round
suspended**



**SASSO 100 round
wall**





