

# SASSO 60 base round adjustable 2 lamps

ceiling

048-31402171S



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Surface	
tilt max 30°	
rotation 360°	
white , RAL 9016 <sup>1</sup>	
Inner colour black	
IP20	
1420 lm	

## LED

3500 K	
CRI ≥ 90	
initial MacAdam ≤ 2 SDCM	
R <sub>g</sub> : 99 , R <sub>f</sub> : 90 , R <sub>(1-15)</sub> : 89	
MR 0.7	
MDER 0.64	

## Optical

spot	
beam angle 15°	
UGR ≤ 13	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	

## Electrical


non DIM	
220-240 V	
system 20.8 W	
system 68 lm/W <sup>3</sup>	
PC1	

## Physical


length 260 mm	
width 80 mm	
height 81 mm	
0.75 kg	

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator



SASSO 60 base

round

adjustable 2 lamps

ceiling

048-31402171S



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	39
B13	63
B16	79
C10	63
C13	101
C16	126

