

SASSO 60 round downlight

suspended

048-31202174S



Project / Type

Notes

Count / Date



General

Ceiling , Suspended
white , RAL 9016 ¹
Inner colour matt silver
IP20
791 lm

LED

3500 K
CRI \geq 90
initial MacAdam \leq 2 SDCM
R_g: 99 , R_f: 90 , R_[1-15]: 87
MR 0.6
MDER 0.54

Optical

spot
beam angle 15°
UGR \leq 13
PstLM \leq 1.0 ²
SVM \leq 0.4 ²

Electrical


non DIM
220-240 V
system 10.4 W
system 76 lm/W³
PC1

Physical

diameter 72 mm
height 75 mm
0.7 kg

Cylindrical spotlight in die-cast aluminium; surface white powder coated; Inner colour lacquered in matt silver; pendant fitting with 1500mm suspension, incl. feed (white), can be individually shortened; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 3500 K; binning initial MacAdam \leq 2 SDCM; CRI \geq 90; energy efficient LEDs with high CRI; incl. high quality lens system; precise radiation characteristic with 15° beam; UGR \leq 13; degree of protection IP20; PC1; 220-240 V; incl. converter, non dimmable; converter included in canopy; canopy for through wiring; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Lighting calculator



SASSO 60 round downlight

suspended

048-31202174S



Project / Type

Notes

Count / Date

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	46
B13	59
B16	74
B20	92
C10	74
C13	94
C16	119
C20	149